

NPX

15D/17/20/22

ELECTRIC 24/36 VOLT
3000 / 3500 / 4000 / 4500 lbs.
(1350 / 1600 / 1800 / 2000 kg)



STANDARD SPECIFICATIONS

15D/17/20/22

Manufacturer's Designation		NPX 15D	NPX 17	NPX 20	NPX 22
Load Capacity / Rated Load	lbs(kg)	3000 (1350)	3500 (1600)	4000 (1800)	4500 (2000)
Height Overhead Guard	in(mm)	95 (2413)	95 (2413)	95 (2413)	95 (2413)
Frame Width	in(mm)	40.25 (1022)	40.25 (1022)	40.25 (1022)	40.25 (1022)
Right Angle Stack (48"L x 40"W, Add 8" for Clearance)	in(mm)	106 (2692)	93.0 (2362)	93.0 (2362)	98.2 (2494)
Outside Turning Radius	in(mm)	76.14 (1934)	66.5 (1689)	66.5 (1689)	69.7 (1770)
Travel speed unloaded	mph (kph)	7.5 (12.0) / 7.5 (12.0)	7.5 (12.0)	7.5 (12.0)	7.5 (12.0) / 7.5 (12.0)
Power Unit		Dual 24 volt / 36 volt	36 volt	36 volt	Dual 24 volt / 36 volt

Standard Equipment

Key switch • Load backrest extension • Electronic horn • Rear overhead guard post protection
Heavy-duty battery rollers • Battery retainers • Lever type battery connect-disconnect
Metal capacity plate

For more information on this model and the full line of CLARK Forklifts, find you local CLARK Dealer at www.clarkmhc.com.

